

CLAIMS

PAGE 11

We claim:

- sub 1
1. A holding base system comprising
a base unit including
a platform,
means for securing said platform to a surface,
an exteriorly splined shaft extending from said platform, and
an article holder including
an interiorly splined socket fitting over and cooperating with said
exteriorly splined shaft, and
bifurcated arms extending from opposite sides of said sprocket.
 2. A holding base system as in Claim 1, wherein
said bifurcated arms each have at least one flexible vane extending inwardly
towards an opposite one of said bifurcated arms and towards said socket.
 3. A holding base system including
a pair of base units;
means interconnecting said pair of base units;
an article holder secured to each of said base units; and
means for adjusting the angular relationship of at least one of said article holders
relative to the base unit to which said one article holder is secured.
 4. A holding base system as in Claim 3, wherein
said article holders each includes article securement means; and wherein

10035290-010302

B1
cont.

at least one of said article securement means includes strap means to pass over an article to be secured and to be fastened to said securement means.

5. A holding base system as in Claim 4, wherein
said article holders each includes article securement means; and wherein
at least one of said article securement means includes a pair of bifurcated arms.

6. A holding base system as in Claim 5, wherein
each of said article securement means includes a pair of bifurcated arms.

7. A holding base system as in Claim 6, wherein
each of said bifurcated arms includes at least one flexible vane extending towards
the other of said bifurcated arms and towards the base unit to which the
bifurcated arms are secured.

8. A holding base system comprising
a base unit including
a platform,
means for securing said platform to a surface;
an exteriorly splined shaft extending from said platform;
a cross-bar having an interiorly splined socket fitting over and cooperating
with said exteriorly splined shaft extending from said platform and having
at least one exteriorly splined shaft extending therefrom; and
at least one article holder having an interiorly splined socket fitting over
and cooperating with at least one exteriorly splined shaft extending from
said cross bar.

10035290-010302

Add
fs